

PQ - OBD

2G/4G CELLULAR

Plug and Play OBDII GPS Tracker



PQ-OBD is a compact and economical, yet feature rich GPS/GLONASS tracking device available in 2G or 4G Cat-M1/NB-IoT versions.

PQ-OBD simply plugs into the vehicle's OBDII port, meaning zero install cost. Perfect for rental fleets where a hard-wired install is not desirable.

FEATURES

2G or 4G Cat-M1/NB-IoT Modem

High Sensitivity GPS with LNA

3D Accelerometer

Easy plug-and-play install

Geo-fencing and Alerts

Electronic Odometer, scheduled maintenance reminders and log books

APPLICATIONS



Vehicle and Fleet tracking



Powered Asset tracking



Electronic Odometer



Tax and FBT reporting



Maintenance reminders



Anchoring and Security of assets

PQ - OBD

MECHANICAL SPECIFICATIONS

Compact Housing	The compact polycarbonate housing snaps together for easy provisioning.
Dimensions	L 71 x W 46 x H 24 mm
Operating Temperature	-20°C to +60°C

POWER

Input Voltage	OBDII Power Absolute Max 36V OBD Connector works in 24V vehicles
Self-resetting fuse	The PQ-OBD passes stringent automotive power “load dump” tests to ensure that it will continue to operate in the harshest electrical systems. A built-in self-resetting fuse makes installation easy and safe.

OTHER

Internal Memory	Sufficient memory to store over 50,000 records. Normally data is sent to the server immediately but if the device is out of range there is space to ensure no data is lost –for many weeks of driving!
3-axis accelerometer	Allows the PQ-OBD to detect harsh driving events, and to go to ‘sleep’ when not moving, resulting in extremely low standby current

CONNECTIVITY

SIM Size	Nano (4FF) size cellular SIM Card
2G or 4G	PQ-GPS can be manufactured for specific markets around the world.
4G Modem	UBLOX SARA-R410-02B This modem can be configured to operate on either LTE-CatM1 or LTE-NB1 networks. Supported LTE bands:1*, 2, 3, 4, 5, 8, 12, 13, 18, 19, 20, 25, 26*, 28 (* roaming bands)
2G Modem	2G: SARA-G350-02S-01

GPS TRACKING

GPS and Cellular Antenna	Internal GPS and cellular antennas tuned by RF laboratories for optimal performance. Having the antennas inside the housing makes for very simple and quick installation.
GPS/GLONASS Tracking	UBLOX EVA-M8 GPS Module Concurrent GPS and GLONASS tracking 72 channel high sensitivity receiver-167dBm industry leading tracking performance
AssistNowOffline	AssistNowOffline aiding data or extremely fast time-to-first-fix and performance in urban canyon environments
Low Noise GPS Amplifier (LNA)	GPS signals are boosted by a special low-noise amplifier (LNA). This allows operation where normal units will fail to receive GPS signal

FIRMWARE SMARTS

OTA Configuration	PQ-OBD can be remotely configured and updated OTA (over the air)
Auto-APN	Auto-APN allows the PQ-OBD to analyse the SIM card and select the correct APN details from a list that is pre-loaded in the device's firmware.
Flexible Logging Parameters	PQ-OBD trip logging is flexible and can be configured to log based on a variety of parameters including: Elapsed time, Distance travelled, Change in heading, Change in speed, On Stationary, Accelerometer events (harsh driving)
Accident and Rollover Detection	PQ-OBD uses the built-in accelerometer to detect high G impacts such as accidents and rollovers and reports these events to the server for emergency alerting.
Harsh Driving	<p>PQ-OBD automatically calibrates its built-in 3 axis accelerometer and uses this to detect harsh driving events:</p> <ul style="list-style-type: none">•Excessive acceleration•Harsh braking•Cornering at speed <p>These events are logged in the PQ-OBD along with additional event statistics that allow back-end server platforms to perform sophisticated driver profiling and scoring.</p>
Accident Data	PQ-OBD keeps a second-by-second "black box" recording of valuable GPS and accelerometer data for a two hour window. This data can be automatically uploaded to the server when an accident is detected, or it can be requested manually.

CERTIFICATIONS

Geo-Fences	<p>PQ-OBD has the capacity to hold hundreds of geo-fences. A future firmware update will enable the PQ-GPS to download geo-fences from the server. PQ-GPS could use this geo-fence information to:</p> <ul style="list-style-type: none">•Implement arrival and departure alerts•Implement "No-Comms" areas
-------------------	--